TMR MIXER

R

-0

00000

M40S

13. 10

ROVIBEC

DIRECT DRIVE MIXER

«PLUG & MIX» SERIES



DESCRIPTION

A **«Plug&Play»** conception. A single unit, all-in and ready to use!

- Compact, efficient and energy-saving
- Made of Canadian steel 44W
- Tub covered with a stainless steel liner of 30"(76 cm)
- A 3/4" (19 mm) auger
- A Direct Drive motor
- A Heavy Duty planetary
- An enclosed and lubrication free PTO
 An optional 2-years or 5-years warranty period, parts and labour

SCALE

A mixer from 353ft³ to 432ft³ designed to last: more performance, less maintenance!

DETAILS



HARDOX AUGER


TECHNICAL SPECIFICATIONS

CAPACITY	353 pi ³ (10m ³) without extension
	400pi3 (11.32m3) with 12" (30.5 cm) rubber extension
	432pi ³ (12.23m ³) with 18"(45.7 cm) rubber extension
RUBBER EXTENSION	A 12" (30.5 cm) or 18" (45.7 cm) rubber extension is available as an option
MOTORIZATION	High efficiency Direct Drive motor with variable speed
	40 HP as standard, 50HP as an option
	Left, right or back motorization
CONTROL PANEL AND DRIVE	Manual panel 30 HP 40HP or 50 HP
	Drive control up to 4 speeds motor for auger rotation
PLANETARY	Heavy Duty planetary
PTO	Enclosed PTO, lubrication free
SCALE AND LOADCELLS	DINAMICA or DIGISTAR scale and 4 loadcells, up to 10 000Lbs (4535 Kg)
DISCHARGE DOOR	The discharge door is controlled by an electric cylinder
	1500 Lbs (680 Kg) torque with Amp management
KNIVES	6 knives and 2 strongbacks included
STEEL	Canadian steel 44W, ¾"(19mm) thick for the floor and ¼" (6mm) for the walls
	Auger ¾"(19mm)
DIMENSIONS (L X l X H) WITHOUT EXTENSION	150'' ¾ X 89'' ^{7/8} X 97'' ¾ (383,2 cm X 228,4 cm X 247.3 cm)
WEIGHT	7436 Lbs (3373 Kg)

ELECTRIC CYLINDER



Optional



150 7/8

ADJUSTABLE LEGS

27 I/8 688mm

MANUAL CONTROL PANEL



